

9.6 V CORDLESS HYDRAULIC CRIMPING TOOL



B 35-50

general features

Crimping force kN	Dimensions mm			Battery Ni-MH	Weight kg (with battery)
	length	height	width		
35	372	108	66	9.6 V 2.0 Ah	2,4

**9.6V
2.0Ah
Ni-MH**

New

MAIN APPLICATIONS - max section mm²

L.V. lugs and splices	Insulated terminals	End sleeves	"C" sleeve Connectors
150	50	50	35

STORAGE


Type	Dimensions mm	Weight kg	Supplied with the tool	Available upon request
VAL P22	448x306x122	1,4	✳	—

Can be operated with one hand.
Balanced for greater control.
Head rotates by 180° for ease of operation in confined spaces.
The tool is fitted with a maximum pressure valve.
Automatic return of jaws after completion of the crimp.
Automatic return can be stopped at any time to ease positioning.
Extremely quiet, minimal vibration.
Durable moulded body offering high resistance to wear and damage in all operating conditions.
Ni-MH battery; powerful, better environmental compatibility.
Battery condition displayed after every crimping operation and after any battery insertion to show the residual battery power.
Supplied in a robust plastic case to accommodate the tool and all the accessories.

Two batteries and charger included.
Wide selection of crimping dies common to 50 kN Cembre crimping tools.
Application field is the one defined in the table aside. For further details please refer to tables of page 142-146.

The tool is supplied with:

- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- Battery adapter
- Plastic carrying case suitable for storing the tool and accessories




Head rotates by 180° for ease of operation

Sculptured body for optimum comfort

Durable moulded body offering high resistance to wear and damage in all operating conditions



Openable head, ideal for derivations from running conductors



Switch ergonomically designed



Battery condition display



Interchangeable die sets